## Manual Double Miter Bandsaw

GRAUBOU







**Control Panel** 



Specifications

Capacity

Drive

Coolubricator

90 Degrees

**45 Degrees** 

60 Degrees

**Main Motor** 

(Inverter Drive)

**Speed Changes** 

**Angle Cutting** 

(Right/Left)

(Right)

Speeds

Method

Voltage

Weight

INIS

**Blade Size** 

Dimensions

## Features:

- Automatic Shut-off at end of cut
- Adjustable Hydraulic Down Feed
- Inverter Drive Motor for infinitely adjustable blade speed & digital read-out on control panel
- Control Panel swivels for optimal positioning
- Bandsaw blade tension meter read-out allows for the proper tension to be applied with each new blade yielding higher blade life & more accurate cuts
- **Emergency Stop**
- Gearhead Motor provides high torque to drive wheel
- Flood Coolant system with adjustable flow control at guide arm & On/Off switch on main control panel
- 78 Liter Coolant Tank
- Cut-off part length stop
- Adjustable ball bearing guides combined with carbide pads
- Wheel Driven Chip brush for clearing chips from teeth

Excellent Fabrication Bandsaw Cut Single or Bundled Paris Straight or Mitered

SPENCE stributors Ltd.

89 Merit Cres. Winnipeg, MB. R2P 2W5 Ph: (204) 633-6603 (800) 694-4021 Fax: (204) 694-6058

www.spencedistributors.com

Mistir	ng Systems



e-mail: sales@spencedistributors.com

Roller Tables & Stands

Lease Rates: Based on 60 month term with 10% buyout O.A.C

7540-WS-20

7540-WS-20

13"Hx18"W

13" Round

13"Hx10.6"W

12" Round

12.4"Hx7.7"W

8.5" Round

3 Hp.

**Infinitely Variable** 

69-306

Head Swivels Both

**Directions Around Part** 

1-1/4"Wx.045"Tx162"L

88"L"x35"Wx61"H

220V 1Ph 60Hz.

2,150 Lbs