

Manual Double Miter Bandsaws



Features:

- Automatic Shut-off at end of cut
- 2 Feed methods: 1.) Pull Down Head Manually or 2.) Auto Down Feed by Adjustable Hydraulic Cylinder
- **Emergency Stop**
- Infinitely Variable Blade Speed with Digital Read-Out on Control Panel
- Tension Meter assure proper blade tension with each blade change
- Flood Coolant system with adjustable flow control at guide arm & On/Off switch on main control panel
- Inverter Drive Gearhead Motor provides High Torque
- Cut-off part length stop
- Adjustable ball bearing guides combined with carbide pads
- Chip brush for clearing chips from teeth

| Specifi | cations | 7540-WV-275DS | 7540-WV-350DS |
|----------|---------------------------|---|------------------|
| Capacity | 90 Degrees | 4.3"Hx10.3"W | 8.7"Hx13.8"W |
| | | 9" Round | 10.6" Round |
| | 45 Degrees (Right) | 5"Hx7.9"W | 6.3"Hx9.5"W |
| | | 5.9" Round | 9.5" Round |
| | 60 Degrees (Right) | 3.4"Hx3.4"W | 5.9"Hx5.9"W |
| | | 3.5" Round | 6.3" Round |
| | 45 Degrees (Left) | 4.3"Hx6.3"W | 7.1"Hx7.1"W |
| | | 4.3" Round | 8.3" Round |
| Drive | Main Motor | 1-1/2 Hp. | 2 Hp. |
| | Speed Changes | Inverter Drive - Infinitely Variable | |
| | Speeds | 65-280 SFM | |
| | Angle Cutting Method | Head Swivels Around Part in Both Directions | |
| | Blade Size | 1"Wx.035"Tx97"L | 1"Wx.035"Tx125"L |
| | Dimensions | 61"L"x29"Wx41"H | 69"L"x30"Wx43"H |
| | Voltage | 220V 1ph. 60Hz. | |
| | Weight | 800 Lbs. | 905 Lbs. |







Misting Systems

Roller Tables & Stands

SPENCE

stributors Ltd.

89 Merit Cres. Winnipeg, MB. R2P 2W5 Ph: (204) 633-6603 (800) 694-4021

Fax: (204) 694-6058

www.spencedistributors.com

e-mail: sales@spencedistributors.com

Lease Rates: Based on 60 month term with 10% buyout O.A.C